



SLIM PANEL LIGHT - 6"



BENEFITS

- Ultra-slim light design
- Nice and consistent lighting colour with even light distribution
- Quick and easy installation


ADVANTAGES

- Two spring options to match different installation cut-outs
- High colour reducing index


APPLICATION

- Restaurant, Offices, Commercial Hospitals etc.

MEASUREMENT



LIGHT CURVE DIAGRAM



SPECIFICATIONS

FEATURES

Shape	Round
Cut-out	150mm
IP Rated	20
Type	Slim Panel Light
Voltage	100-240 V

LIGHT ATTRIBUTES

Light Output	800 (DL) / 720 (WL) lumen
Beam Angle	112 degree
Color Temperature	6500 K (DL) / 3000 K (WL)
Light Effective/Finish	Day Light / Warm White
Color Rendering Index (CRI)	80
Starting Time	Instant light
Power Factor	>0.7
Lamp Current	60 mA

ROBUSTNESS

Lifetime	25000 hours
Number of Switch Cycle	12,500
Lumen Maintenance	0.9
Average Life (at 5 Hrs/Day)	13 years

DIMENSION

Height	19 mm
Width	165 mm

RATED VALUES

Wattage	12 W
Rated Lumen Flux	800 (DL) / 720 (WL) lm
ESMA Approved	Yes
Certification	CE CB ROHS