



LED Downlight - 4"



BENEFITS

- Die cast aluminum design for excellent heat dissipation
- Designed for anti-glare and comfortable lighting
- Easy installation with terminal connector


ADVANTAGES

- High efficacy
- Rated product can be also used for outdoor applications


APPLICATION

- Commercial, Restaurant, Offices, Hospitals, Shopping Mall etc.

MEASUREMENT



LIGHT CURVE DIAGRAM



SPECIFICATIONS

FEATURES

Shape	Round
Cut-out	100mm
IP Rated	44
Type	LED Down Light
Voltage	220-240 V

LIGHT ATTRIBUTES

Light Output	800 (DL) / 800 (WL) lumen
Beam Angle	112 degree
Color Temperature	6500 K (DL) / 3000 K (WL)
Light Effective/Finish	Day Light / Warm White
Color Rendering Index (CRI)	80
Starting Time	Instant light
Power Factor	>0.7
Lamp Current	50mA

ROBUSTNESS

Lifetime	25000 hours
Number of Switch Cycle	12,500
Lumen Maintenance	0.9
Average Life (at 5 Hrs/Day)	13 years

DIMENSION

Height	50mm
Width	120 mm

RATED VALUES

Wattage	11 W
Rated Lumen Flux	800 (DL) / 800 (WL) lm
ESMA Approved	Yes
Certification	CE CB ROHS